

## Technical Data Sheet

# FUNGIVER Mould and Mildew Remover No. 1780

One-time treatment against mould and mildew and their spores



cova remediation systems

### New Quality

<b>Range of application</b>	For all interior surfaces like wood, masonry, wallpaper, tiles, OSB - and other breathable wooden composite boards. Also suitable for upholstery, carpets, curtains and other fixtures.
<b>Technical qualities</b>	Destroys mould and their spores, as well as bacteria. Readily biodegradable and non-combustible. Good skin compatibility (Dermatest 2009), safe, quick and easy application. Economic, one application is sufficient.
<b>Full declaration</b>	Water, hydrogenperoxide, salicylic acid. All ingredients are used in pharmaceutical quality.
<b>Application method</b>	One application on the affected areas with a suitable spraying device.
<b>Dilution</b>	Delivered ready to use.
<b>Coverage</b>	1 l Mould and Mildew Remover No. 1780 is sufficient for appr. 8 - 12 m <sup>2</sup> (86 - 129 ft <sup>2</sup> ).
<b>Color</b>	Colorless.
<b>Reaction time</b>	Minimum 60 minutes.
<b>Specific gravity</b>	Appr. 1.02 g/cm <sup>3</sup>
<b>Cleaning</b>	Clean equipment immediately after use with water.
<b>Safety information</b>	<p><b>Use Mould and Mildew Remover safely. Always read the label and product information before use.</b></p> <p>P102 Keep out of the reach of children. EUH210 Safety data sheet available on request.</p> <p>Biocidal agent: Hydrogenperoxide 49.9 g/l, salicylic acid 2g/l. 89/542/EWG: Contains Preservatives, &lt;5% bleaching agents on basis of oxygen. <b>baua: Reg.-Nr. N-70542</b></p>
<b>Disposal</b>	According to locally regulated laws. European waste code: 07 06.
<b>Container sizes</b>	0,5 l; 2,5 l; 10 l.
<b>Storage</b>	Cool, dry, frost-free and close lid tightly after use. Shelf life: 24 month. Protect from direct sunlight. Always store in an upright position.

How to use

## **FUNGIVER Mould and Mildew Remover No. 1780**

<b>Application</b>	Apply once on the affected areas with a suitable spraying device (without base metals such as brass, copper etc.). Leave on for at least 60 minutes. Remove deactivated mould or rinse with water. To avoid fast new infestation it is recommendable to spray again after it has dried.
<b>Safety advice</b>	<p>Do not inhale aerosol.</p> <p>Mould can be harmful, therefore the following precautions are absolutely necessary (also on smaller areas):</p> <p>Wear dust mask (e.g. P3) against mould and their spores in the air.</p> <p>Protective gloves and safety glasses to avoid skin and eye contact.</p> <p>Tight closing clothing.</p>
<b>Additional information</b>	<p>Do not store in metal containers.</p> <p>With sensitive materials, a test application on an inconspicuous place is recommendable in order to avoid e.g. unwanted color reactions on textiles.</p> <p>In case of large-scale mould infestation and/or suspicion of hidden mould, please contact an expert e.g. building biologist or specialized company for mould remediation.</p>

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

May 2017