

Technical Data Sheet

KUNOS Finishing Oil No. 240

N means **LIVOS neutral** for the allergy-prone and chemically sensitive

Without orange oil

Application range	In the interior, for maintenance, after-treatment of with LIVOS products oiled countertops, solid wooden furniture, floors and stairs, as well as brushed or profiled wood.
Technical qualities	After polishing semi-glossy, water-repellent surface. Complies with the German Industrial Norm DIN 53 160 for color fastness when exposed to perspiration and saliva.
Full declaration	Isoaliphates, linseed oil - stand oil - natural resin ester, micronized wax, dehydrated castor oil, dehydrated amino sugar and drying agents free of lead. (Co, Mn, Zr)
Colors	002 clear
Application method	By brush or wadded cloth, on large areas with a single disc rotary machine and felt pad. 1-2 applications at temperatures above 18 °C (64 °F).
Coverage	Determine the exact amount needed by doing a test application. 1 liter (1.06 quart.) is sufficient for appr. 100 m ² (1076ft ²), i.e. 10 ml/m ² .
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.
Drying time	At 23°C (73°F) and a relative humidity of 50%: 16 - 24 hours. Final durability is reached after 4 weeks. At higher temperatures, please consider shorter drying times and polish more quickly. At lower temperatures and higher humidity, please consider longer drying times.
Specific gravity	Approximately 0.85 g/ml.
Safety advice	<p>Ensure good ventilation during and after application. Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with KUNOS Finishing Oil No. 240 in an airtight metal container or in water, as there is a danger of combustion caused by the plant oil content. The product itself will not combust spontaneously.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains Cobalt (2+) salts. Can cause allergic reactions.</p>
Disposal	According to locally regulated laws.
Container Size	0.25 l; 0.75 l; 2.5 l; 10 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Transfer unused product into a smaller container for storage in order to minimize excess air.

How to use

KUNOS Finishing Oil No. 240

Counter tops, Stairs

Preparation:

Oiled wooden surfaces must be dry, clean and free of dust.

Sand any existing watermarks with 320 grain and treat the surface 1 – 2x with the initial product until the gloss level of the remaining area is reached.

Processing:

Stir thoroughly. Remove possible skin formed on surface.

Test application!

Apply Finishing Oil generously and wipe off excess oil after 5 minutes with a lint-free cotton cloth. The next day (after 16 hours), apply the Finishing Oil generously again and polish after 5 minutes.

Floors

On oiled surfaces, which have uniform gloss, spread Finishing Oil drop by drop (1 TS (Tablespoon) = 5-8 g/m²). Polish immediately with a grain free pad (beige or felt) wetted with Finishing Oil, or with a polishing- pad or -machine. Stripes should be avoided; check in the backlight. The whole procedure should be repeated if necessary.

Cleaning and Maintenance

Clean with TRENA pH-Neutral Cleaner No. 556 diluted in water and with a moist but not wet cloth. Every 4th to 5th cleaning should be done with GLANOS Natural Liquid Wax Cleaner No. 559 instead of TRENA.

After-treatment depending on the usage, usually 1- 2 times a year with KUNOS Maintenance No. 1862, if the surface looks matt.

Important tips

With brushed wooden surface, or when the surface was profiled with special tools, apply Finishing Oil generously 1x and spread on the surface standing oil after 5 minutes with a hard brush or similar. Then apply 2 sparing coats with intermediate drying.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

January 2016